Feed Management. PRECISELY.



EZ 2500 V Standard Offering



Provides durability, quality, and simplicity

- Provides basic features for most applications
- Hold Key to "freeze" the displayed weight when moving the equipment
- Remote display port
- Standard offering with every mixer
- Slimline profile fits nearly anywhere



Utilize basic recipe and batching capabilities

- Build different recipes for multiple pens
- Eliminates the need for feed sheets
- Enter rations by three different methods
 - Amount per animal
 - Percent per load
 - Amount per load
- Remote display port
- First ingredient resizing allows bales of different weights to be loaded as 1st ingredient and adjusts all other ingredients to compensate for a target final weight



EZ 2400 V 12-8968-20



Ideal for simple feed mixer and general weighing applications

- Alarm light (12-8970-10), horn (12-8969-10), remote transmitter (12-8946-10), or wireless radio can be added
- "Select" and "Function" keys allow utilization of Memory Plus (M+) and Recall Memory (RM) features showing total number of loads, total weight, accumulated and average weight
- Remote display port

EZ 3600 V 15-1205-00



Full Feed Management Indicator

- Program rations at your PC or from the front panel of your indicator
- Compatible with TMR Tracker[®] Feed Management Software
- Internal "alarm light and horn" alerts operator of approaching target weights
- Make "pen call weights" and "head count" changes at the indicator
- Multi-language help messages
- Remote display port

Helm Welding Limited Call for flyer: 519-529-7627 Tel: 519-529-7000 www.lucknowproducts.com Fax: 519-529-3260 www.digi-star.com ©2014 Digi-Star

We reserve the right to modify designs or implement product improvement, without any obligations with respect to goods purchased.

Feed Management. PRECISELY.



Basic Wireless Kit 15-1200-00



EZ 2400 V





Installed in the loader, the Cab Control displays the same weight information as the scale.

- Cab Control displays the same weight information as the scale
- Increases load accuracy and efficiency
- Operator control of Tare, Zero, Net, or Gross weights
- Range up to 1000 ft. (depending on location)

Remote Display Options

RD 2500 V 14-0047-00

Bubler * 23850

- Large 1.7" LCD display with alarm light
- Bright LCD backlight for dark or inclement conditions
- Impact resistant window
- Slimline profile

RD 4000 15-1201-00



LUCK NOW

- Large 4" LED ultra bright display
- Viewable from 200 feet
- Lighted load progression bar graph



Optional Accessories*

Remote Transmitter



Set Tare or Zero and select Net or Gross weights from Loader Cab up to 100 ft away

 Advance the ingredient or pen when using batching indicators

Alarm Horn 12-8969-10



 Provides a loud audible alarm for precise loading and unloading

Alarm Light 12-8970-10



 Provides a bright visual for precise loading and unloading

*Not Available for use with EZ 2500

Helm Welding Limited Call for flyer: 519-529-7627 Tel: 519-529-7000 www.lucknowproducts.com Fax: 519-529-3260 www.digi-star.com ©2014 Digi-Star

We reserve the right to modify designs or implement product improvement, without any obligations with respect to goods purchased.