

# Feed Management

## PRECISELY

### EZ 2500 V Standard Offering



#### Provides durability, quality, and simplicity

- Provides basic features for most applications
- Hold Key to “freeze” the displayed weight when moving the equipment
- Remote display port
- Standard offering with every mixer
- Slimline profile fits nearly anywhere

### EZ 2810



#### Added functions to improve Loading and Unloading Efficiency

- Large 1.7” (43 mm) white backlit COG is even easier to read than EZ 2500 V
- Preset Weight function provides improved accuracy and management of loading and unloading
- R Internal “alarm light and horn” alert operator of approaching target preset weights
- Rotation Counter/Timer aids in controlling mix time

### EZ 3410



#### Programmable Mix Batching and Unloading

- Three program methods: Per Cow Basis, Percent Basis, and Total Ingredient Basis
- Preset Weight allows accurate management of loading and unloading.
- 200 ingredient memory capacity, alphanumeric keypad
- First Ingredient Resizing - automatically adjust remaining ingredients
- Ingredient accumulation data is recorded internally, allowing for CSV data file download to PC
- Internal “alarm light and horn” alerts operator of approaching target weights

### TMR 3610



#### Feed Management Indicator

- Program rations at your PC or from the front panel of your indicator
- Compatible with TMR Tracker® Feed Management Software
- Internal “alarm light and horn” alerts operator of approaching target weights
- Make “pen call weights” and “head count” changes at the indicator
- Multi-language help messages
- Keeps up-to-date feed changes or reuse data



TMRTracker® is a registered trademark of Topcon Agriculture Americas.

Helm Welding Limited  
Call for flyer: 519-529-7627

Tel: 519-529-7000  
www.lucknowproducts.com

Fax: 519-529-3260  
www.digi-star.com  
©2017 Digi-Star

We reserve the right to modify designs or implement product improvement, without any obligations with respect to goods purchased.

# Feed Management

## PRECISELY

### EZ 2500 V



### CC 400



### Basic Wireless Kit 15-1200-00

Installed in the loader, the Cab Control displays the same weight information as the scale.

- Cab Control displays the same weight information as the scale
- Increases load accuracy and efficiency
- Operator control of Tare, Zero, Net, or Gross weights
- Range up to 1000 ft. (depending on location)

### Remote Display Options

### RD 2500 V 14-0047-00



- Large 1.7" LCD display with alarm light
- Bright LCD backlight for dark or inclement conditions
- Impact resistant window
- Slimline profile

### RD 4000 15-1201-00



- Large 4" LED ultra bright display
- Viewable from 200 feet
- Lighted load progression bar graph

### Optional Accessories\*

### Remote Transmitter 12-8946-10



Set Tare or Zero and select Net or Gross weights from Loader Cab up to 100 ft away

- Advance the ingredient or pen when using batching indicators

### Alarm Horn 12-8969-10



- Provides a loud audible alarm for precise loading and unloading

### Alarm Light 12-8970-10



- Provides a bright visual for precise loading and unloading

\*Not Available for use with EZ 2500



Cab Control™ is a trademark of Topcon Agriculture Americas.

Helm Welding Limited  
Call for flyer: 519-529-7627

Tel: 519-529-7000  
www.lucknowproducts.com

Fax: 519-529-3260  
www.digi-star.com  
©2017 Digi-Star

We reserve the right to modify designs or implement product improvement, without any obligations with respect to goods purchased.